



**2019 CATALOGUE**

GENERATORS & PRESSURE WASHERS



HAND TOOLS  
**INDEX**

FORD MOTOR COMPANY / FORD TOOLS.....02

FORD TOOLS AFRICA / OUR VISION .....03

GENERATORS .....04

PRESSURE WASHERS .....09

CONTACT US.....10



**FORD MOTOR COMPANY**

On June 16, 1903, Henry Ford established the Ford Motor Company in Detroit, Michigan. Over its 111 years of history, Ford grew to become one of the largest international companies in the world. Today, its products and innovation are still at the forefront of the industry, revolutionizing the future of electrical vehicles. Ford was recognized as one of the 50 most Innovative Companies by FastCompany magazine.



**FORD TOOLS**

Our team of experts at NINE HKG Ltd., with over 20 years of experience in the development and production of quality tools, has joined forces with the Ford Motor Company in order to develop a unique line of products that honors the legacy established by Henry Ford in terms of production of dependable and affordable goods. NINE HKG Ltd., as the global official licensee of the Ford Tools Lineup, has appointed several distributors worldwide in order to better serve the specific needs of countries and regions around the globe.



A man wearing a cap and a t-shirt with the 'Ford TEAM' logo is working on a car. In the foreground, there is a large, open toolbox with the 'Ford' logo on its side. The entire image has a blue color overlay.

## AFRICA FORD TOOLS

### OUR VISION

The Ford Tools concept was initiated in 2013, Africa Ford Tools (Pty) Ltd. has been awarded the Official License for Africa.

Our vision is to be Africa's leading brand of choice, customer preferred marketer and distributor of Hand Tools, Power Tools and service solutions to the automotive, industrial, retail and wholesale markets.

We are pleased to bring this concept of quality and excellence to your business.







# INVERTER GENERATOR

## FG2500iS



**MODEL**  
FG2500iS  
**Peak Output**  
2200W  
**Rated Output**  
2000W

### SPECIFICATIONS

ENGINE	
Displacement (cc)	98cc
Engine Type	Single cylinder, 4-Stroke, OHV, Air Cooled
Horse Power	3.5hp
Run Time @ 50% Load	5h

CONTROL PANEL	
Parallel	N/A
Outlets	With European Outlets
DC	Yes
USB	Yes
Overload Breaker	Yes
Rubber Outlet Dust Covers	Yes

### CERTIFICATIONS

CE	Yes
oll	Yes

### OVERALL DESIGN

Size (mm)	555x325x490
Multifunctional Switch	Engine , Choke, Fuel in One Swtich
Fuel Tank Size (L / Gal.)	4.5L /1.18Gal.

### OTHER FEATURES

Starter Type	Recoil
THD%	≤3%THD

### PACKAGING DETAILS

Carton Type	Color Box
Gross Weight (kg / lbs.)	23.5kg/ 51.8 lbs

### FRIEGHT QTY (with Pallet)

20' Container	304
40' Container	624
40' HQ Container	735
MOQ	One 20' Container



## FG4050P/FG4050PE

## MODEL

FG4050P/ FG4050PE

## Peak Output

3500W

## Rated Output

2500W



## SPECIFICATIONS

ENGINE	BFT	
Displacement (cc)	208cc	
Engine Type	Single cylinder, 4-Stroke, OHV, Air Cooled	
Run Time @ 50% Load	13.5h	11h
Low Oil Sensor	Yes	

CONTROL PANEL	“M” Panel Type	
Outlets	With European Outlets	One 120V, 20A duplex + One 120V/240V 30AMP Twist-lock Outlet+ one 120V 30AMP RV
Frequency	50Hz	60Hz
AVR	Yes	
3 in 1 Meter [Volts/ Frequency/ Hours]	Yes	N/A
Hour Meter(LCD)	N/A	Yes
Circuit Breakers	Yes	
Rubber Outlet Dust Covers	Yes	

## CERTIFICATIONS

CE-EMC	Yes	N/A
EPA3	N/A	Yes
CARB	N/A	Yes
CSA	N/A	Yes
EU-II	Yes	N/A

## OVERALL DESIGN

Frame Style	Ø25 mm
Frame Finish	Powder Coated
Wheel & Tire Type	N/A
Fuel Tank Size (L / Gal.)	15 / 4

## OTHER GENERATOR FEATURES

Fuel Gauge	Yes	
Starter Type	Recoil	Recoil / Electric
Battery Type	N/A	Yes
Battery Included	N/A	

## PACKAGING DETAILS

Carton Type	Color Box
Gross Weight (kg / lbs.)	54.5 / 120.2

## FRIEGHT QTY (with Pallet)

40HQ	352 With Pallet / 475 Without Pallet
MOQ	40ft Containers

## FG7750E

**MODEL**  
FG7750E  
**Peak Output**  
6500W  
**Rated Output**  
5000W

Clean Power, Ideal for sensitive electronics less than 5% THD, only for 50Hz Generator



### SPECIFICATIONS

ENGINE	BFT	
Displacement (cc)	420cc	
Engine Type	Single cylinder, 4-Stroke, OHV, Air Cooled	
Run Time @ 50% Load	14h	12.5h
Low Oil Sensor	Yes	

CONTROL PANEL	Removable(Panel Extension Cord Included)	
Outlets	With European Outlets	Two GFCI outlets + One 120V/240V Twist-lock Outlet
Frequency	50Hz	60Hz
AVR	Yes	
3 in 1 Meter [Volts/ Frequency/ Hours]	Yes	N/A
Hour Meter(LCD)	N/A	Yes
Circuit Breakers	Yes	
Rubber Outlet Dust Covers	Yes	

### CERTIFICATIONS

CE-EMC	Yes	N/A
EPA3	N/A	Yes
CARB	N/A	Yes
CSA	N/A	Yes
EU-II	Yes	N/A

### OVERALL DESIGN

Frame Style	Ø38 mm
Frame Finish	Powder Coated
Wheel & Tire Type	2 x 10" Chrome Plated Wheel (F150 Style) Never Flat PU Foam Tire
Fuel Tank Size (L / Gal.)	26 / 6.8

### OTHER GENERATOR FEATURES

Fuel Gauge	Yes
Starter Type	Recoil / Electric
Battery Type	N/A 12V 14Ah
Battery Included	N/A Yes

### PACKAGING DETAILS

Carton Type	Color Box
Gross Weight (kg / lbs.)	100 / 220.4

### FRIEGHT QTY (with Pallet)

40HQ	180
MOQ	40ft Containers



## FG9250E



**MODEL**  
**FG9250E**  
**Peak Output**  
**7500W**  
**Rated Output**  
**6000W**

Clean Power, Ideal for sensitive electronics less than 5% THD, only for 50Hz Generator

## SPECIFICATIONS

ENGINE	BFT	
Displacement (cc)	420cc	
Engine Type	Single cylinder, 4-Stroke, OHV, Air Cooled	
Run Time @ 50% Load	12.5h	10.5h
Low Oil Sensor	Yes	

CONTROL PANEL	Removable (Panel Extension Cord Included)	
Outlets	With European Outlets	Two GFCI outlets + One 120V/240V Twist-lock Outlet
Frequency	50Hz	60Hz
AVR	Yes	
3 in 1 Meter [Volts/ Frequency/ Hours]	Yes	N/A
Hour Meter (LCD)	N/A	Yes
Circuit Breakers	Yes	
Rubber Outlet Dust Covers	Yes	

## OVERALL DESIGN

Frame Style	Ø38 mm
Frame Finish	Powder Coated
Wheel & Tire Type	2 x 10" Chrome Plated Wheel (F150 Style) Never Flat PU Foam Tire
Fuel Tank Size (L / Gal.)	26 / 6.8

## OTHER GENERATOR FEATURES

Fuel Gauge	Yes
Starter Type	Recoil / Electric
Battery Type	N/A 12V 14Ah
Battery Included	N/A Yes

## PACKAGING DETAILS

Carton Type	Color Box
Gross Weight (kg / lbs.)	106 / 233.7

## FRIEGHT QTY (with Pallet)

40HQ	180
MOQ	Two 40ft Containers

## CERTIFICATIONS

CE-EMC	Yes	N/A
EPA3	N/A	Yes
CARB	N/A	Yes
CSA	N/A	Yes
EU-II	Yes	N/A



## FD6700E



**MODEL**  
**FD6700E**  
**Peak Output**  
**5000W**  
**Rated Output**  
**4500W**

Clean Power, Ideal for sensitive electronics less than 5% THD, only for 50Hz Generator

## SPECIFICATIONS

ENGINE	BFT	
Displacement (cc)	418	
Engine Type	Single cylinder, 4-Stroke, OHV, Air Cooled	
Run Time @ 50% Load	7h	6.5h
Low Oil Sensor	Yes	

CONTROL PANEL	" M" Panel Type	
Outlets	2X 16A 250V Blue Schuko (IP44), 1 X CEE Socket 230V 32A (Industrial type)	2X 120V 20A Duplex Outlets, 1X 120/240V AC 30A Twist-lock (NEMA L14-30)
Frequency	50Hz	60Hz
AVR	Yes	
3 in 1 Meter [Volts/ Frequency/ Hours]	Yes	Yes
Hour Meter(LCD)	N/A	N/A
Circuit Breakers	Yes	
Rubber Outlet Dust Covers	N/A	

## CERTIFICATIONS

CE-EMC	Yes	N/A
EPA3	N/A	N/A
CARB	N/A	N/A
CSA	N/A	N/A
EU-II	N/A	N/A

## OVERALL DESIGN

Frame Style	Ø32 mm
Frame Finish	Powder Coated
Wheel & Tire Type	10" x 2 Chrome Plated Wheel (F150 Style) Never Flat PU Foam Tire
Fuel Tank Size (L / Gal.)	14 / 3.7

## OTHER GENERATOR FEATURES

Fuel Gauge	Yes
Starter Type	Electric
Battery Type	12V 36Ah
Battery Included	Yes Yes

## PACKAGING DETAILS

Carton Type	Color Box
Gross Weight (kg / lbs.)	95 / 209.4

## FRIEGHT QTY (with Pallet)

40HQ	168
MOQ	Two 40ft Containers





## FPWG2700H-J / FPWG3100H-J

**MODEL**

FPWG2700H-J / FPWG3100H-J

**RATED MAX. PRESSURE - PSI / Bar**

4200PSI

186/214BAR

**RATED MAX. FLOW - GPM / L/m**

522L/h

568L/h

**RATING STANDARD**

PWMA

**SPECIFICATIONS**

ENGINE	
Displacement (cc)	208cc
Horse Power	7HP
Engine Type	BFT 4-Stroke, Single cylinder OHV, Air cooled
Run Time @ 50% Load	TBA
Oil Capacity	0.6L
Low Oil Sensor	Yes
Starter Type	Recoil start only with FORD exclusive recoil cap

OVERALL DESIGN	
Frame Style	Hand Truck (1 1/4" Tubing) POWDER COATED Fold Down Handle
Wheel Type	10"x3" PU Foam Wheel
Axle	Short / Hitch-Pin
On-Board Detergent Container / Bottle Holder	1-1/4 gal - Two single 3/5 Detergent Tank

PUMP	
Type	3-Piston Axial Cam, Aluminum Head
Manufacturer	AR
Life Expectancy	100h min. / 120h min.
a. Thermal Relief Valve	Yes -140°F
b. Chemical Injector	Low Pressure Venturi (HP Side)
c. EZ-Start Pump Valve	Built-In
d. Pressure / Flow Control Knob	NA
e. Pressure Relief Valve (Resettable)	NA

CERTIFICATIONS	
CE	YES
EPA3	YES
European Emissions Standard	YES

**ACCESSORIES**

HP Hose	1/4" ID x 25', Black PVC Outer Skin, Nylon Braided, M22 Couplers	5/16" ID x 30', Black PVC Outer Skin, Nylon Braided, M22 Couplers
Trigger Gun	248BAR Gun Rear Entry, M22-M Inlet, Chrome-Plated Steel Tubing	
Spray Wand	20" Chrome Plated, M22 Connection, 1/4" QC Coupler	20" Stainless Steel, M22 Connection, 1/4" QC Coupler
Nozzles	4 QC Nozzles (0°, 15°, 40°, Standard Soap Nozzle)	5 QC Nozzles (0°, 15°, 25°, 40°, Soap Nozzle)
Engine Oil	10W30 20oz.	
Other	PP 30%GF Accessory Panel	
	NA	PP 30%GF Turbo Nozzle Holder

**CONTACT US**



*- Quality Starts and Stops Here -*

[www.gaydonmotorspares.com](http://www.gaydonmotorspares.com)